

# MiaSolé FLEX SERIES—03W

## CIGS Flexible Modules: High Power Density in a Flexible Form Factor

### KEY FEATURES

- ▶ Record efficiency levels in a flexible form factor
- ▶ Low installed weight at less than 2.0 kg/m<sup>2</sup> (<0.5 lb/ft<sup>2</sup>)
- ▶ No penetrations, ballast or racking required
- ▶ Applicable for high wind load and high seismic hazard areas
- ▶ Bypass diodes reduce PV system shading losses
- ▶ Directly bonds to many approved surfaces

### RELIABILITY AND SAFETY

- ▶ IEC 61646, IEC 61730, IEC 62716, Australia CEC
- ▶ UL 1703, cUL 1703
- ▶ UL Class A over TPO - slope up to 2.5°

### WARRANTY


- ▶ 5 year workmanship
- ▶ 10/25 year warranty against power loss



# MiaSolé FLEX SERIES

## FLEX-03W SERIES CIGS MODULE

### ELECTRICAL PERFORMANCE AT STC<sup>1</sup>



			FLEX-03 470W	FLEX-03 480W	FLEX-03 490W	FLEX-03 500W	FLEX-03 510W
Nominal Power	$P_{MPP}$	[W]	470	480	490	500	510
Aperture Efficiency	$\eta$	[%]	15.4%	15.7%	16.0%	16.4%	16.7%
Power Output Tolerance		[W]	+10/-0	+10/-0	+10/-0	+10/-0	+10/-0
Maximum Power Voltage	$V_{MPP}$	[V]	58.5	59.0	59.5	60.0	60.6
Maximum Power Current	$I_{MPP}$	[A]	8.04	8.13	8.23	8.33	8.42
Open Circuit Voltage	$V_{OC}$	[V]	73.9	74.2	74.5	74.8	75.1
Short Circuit Current	$I_{SC}$	[A]	9.40	9.40	9.40	9.40	9.40
Maximum Series Fuse Rating		[A]	25				
Maximum System Voltage (IEC/UL)		[V]	1000/1000				

<sup>1</sup>Standard Test Conditions (STC): 1000 W/m<sup>2</sup>, 25°C cell temperature, AM 1.5 spectrum

### THERMAL CHARACTERISTICS

NOCT	[°C]	48
Temperature Coefficient of $P_{MPP}$	[%/°C]	-0.38
Temperature Coefficient of $V_{OC}$	[%/°C]	-0.28
Temperature Coefficient of $I_{SC}$	[%/°C]	0.008

### PHYSICAL AND MECHANICAL SPECIFICATIONS

Length	2585 mm (101.8 in)
Width	1293 mm (50.9 in)
Thickness, Maximum at J-Box*, Module	17 mm (0.7 in), 2.5 mm (0.1 in)
Weight (Module without adhesive)	5.5 kg (12.2 lb)
Weight (Module with adhesive)	6.6 kg (14.6 lb)
Weight/Area (Module without adhesive)	1.7 kg/m <sup>2</sup> (0.3 lb/ft <sup>2</sup> )
Weight/Area (Module with adhesive)	2.0 kg/m <sup>2</sup> (0.4 lb/ft <sup>2</sup> )
Junction Box Type	IP68
Cable Connections	Amphenol Technology Shenzhen (E346053)
Cell Type	Copper Indium Gallium Diselenide (CIGS)
Warranty**	5 year workmanship; 10/25 year power output
Certifications	UL 1703, IEC 61646, IEC 61730, UL Class A over TPO - slope up to 1", cUL 1703, IEC 62716, Australia CEC
Packaging Info	10 modules per crate, 40 modules per pallet, 320 modules per 20' ISO container, 640 modules per 40' ISO container

\*2.5 mm (0.1 in) for the rest of the module with adhesive

\*\*1.6 mm (0.06 in) for the rest of module without adhesive

\*\*Please see full warranty for details

Made in the USA and China



2590 Walsh Avenue, Santa Clara, California 95051, USA  
1.408.919.5700 info@miasole.com www.miasole.com

MiaSolé and the MiaSolé logo are registered trademarks.  
©2018 MiaSolé. All rights reserved. Specifications included in this datasheet are subject to change without notice.  
MiaSolé Approved for Public Release.  
Part Number 990-191947-00\_5