

# MiaSolé SOLARRIDE

## SolarRide Transportation Kits: Solar Power Optimized for Transportation

A SolarRide Kit consists of solar modules, an optimized charge controller, and cables. The solar module is a FLEX Series module is a CIGS-based flexible thin-film solar module that is thin, flexible, shatterproof and provides one of the highest efficiencies on the market today, at up to 17%. The kits include a range of sizes and powers of FLEX modules to accommodate various cab sizes and help you achieve your goals. FLEX modules provide the following benefits for transportation:

- ▶ Adhere directly to the roof with no roof penetrations, eliminating the risk of leaks
- ▶ Thin modules offer superior wind resistance
- ▶ Shatterproof and durable
- ▶ Low installed weight at less than 2.0 kg/m<sup>2</sup> (<0.5 lb/ft<sup>2</sup>)
- ▶ Bypass diodes reduce PV system shading losses
- ▶ Record efficiency levels



### SOLARRIDE KITS\*


	<b>75W Trickle Charger</b>	<b>150W Lift-Gate</b>	<b>180W APU</b>	<b>380W APU</b>	<b>500W APU</b>
Modules	1 FLEX-03N 1.7m	2 FLEX-03N 1.7m	1 FLEX-03W 1m	2 FLEX-03W 1m	1 FLEX-03W 2.6m
Charge Controller	8 Amp	10 Amp	15 Amp	20 Amp	20 Amp 60 Amp
Cables	As Required				

\*Custom solutions available, Average Nominal Power shown


# MiaSolé SOLARIDE KIT COMPONENT SPECIFICATIONS



FLEX-03N 1.7m



FLEX-03W 1m



FLEX-03W 2.6m

## SOLAR MODULE ELECTRICAL PERFORMANCE AT STC<sup>1</sup>

			FLEX-03N 1.7m	FLEX-03W 1m	FLEX-03W 2.6m
Aperature Efficiency	$\eta$	[%]	14.3 – 17.3%	14.7 – 17.4%	15.0 – 17.3%
Nominal Power	$P_{MPP}$	[W]	70 – 85W	160 – 190W	460 – 530W
Power Output Tolerance			+5/-0	+10/-0	+10/-0
Maximum Power Voltage	$V_{MPP}$	[V]	18.1 – 20.9	20.6 – 23.3	58.7 – 65.1W
Maximum Power Current	$I_{MPP}$	[A]	3.88 – 4.07	7.82 – 8.16	7.87 – 8.15
Open Circuit Voltage	$V_{OC}$	[V]	23.2 – 25.5	26.1 – 28.4	74.1 – 79.5
Short Circuit Current	$I_{SC}$	[A]	4.67 – 4.47	9.28 – 8.93	9.23 – 8.94

<sup>1</sup>Standard Test Conditions (STC): 1000 W/m<sup>2</sup>, 25°C cell temperature, AM 1.5 spectrum

## SOLAR MODULE PHYSICAL AND MECHANICAL SPECIFICATIONS

	FLEX-03N 1.7m	FLEX-03W 1m	FLEX-03W 2.6m
Length	1710 mm (67.3 in, 5ft 7.3in)	1010 mm (39.8 in, 3ft 3.8in)	2585 mm (101.8 in, 8ft 5.8in)
Width	348 mm (13.7 in, 1ft 1.7in)	1293 mm (50.9 in, 4ft 2.9in)	1293 mm (50.9 in, 4ft 2.9in)
Thickness, Maximum at J-Box*, Module	17 mm (0.7in) 2.5 mm (0.1in)		
Weight (Module with adhesive)	1.3 kg (2.9 lb)	2.5 kg (5.6 lb)	6.6 kg (14.6 lb)
Junction Box Type	IP68		
Cable Connections	Helios H4 (S&F)		
Cell Type	Copper Indium Gallium Diselenide (CIGS)		

## CHARGE CONTROLLER SPECIFICATIONS

		8 Amp		10 Amp		15 Amp		20 Amp		60 Amp			
Battery Voltage	[V]	12V	24V	12V	24V	12V	24V	12V	24V	12V	24V	36V	48V
Maximum Solar Power	[W]	105W	210W	150W	300W	200W	400W	250W	500W	800W	1600W	2400W	3200W
Maximum Charging Current	[A]	8		10		15		20		60			



2590 Walsh Avenue, Santa Clara, California 95051, USA  
1.408.919.5700 info@miasole.com www.miasole.com

Made in the USA and China

MiaSolé and the MiaSolé logo are registered trademarks.  
©2019 MiaSolé. All rights reserved. Specifications included in this datasheet are subject to change without notice.  
MiaSolé Approved for Public Release.  
Part Number 302-206968-00\_A